



**TRACK WRENCH®**

## Digital Torque Tester (EMTT---)

The EcoTorq Series desktop torque tool, accurate and durable tester. Low cost, great accuracy, high quality, ease of use. The EMTT testers are well suited for hand or power tool validation or certification\*.

Rundown fixtures are provided for power tool testing. The creative design of the housing provides for easy bolting to a bench for tool testing.

The range of EDTT tester models is from 0,5 Nm to 2200Nm

### Main Features:

- 1st Peak, Peak Hold and Track mode selectable
- Accuracy  $\pm 1\%$  (CW)
- Digital torque value readout
- Multiple functions including, "Torque Setting", "Unit Setting", "Mode Setting", "Data Storage", "Data Clear".
- CW and CCW operation
- Buzzer and LED indicator n Engineering units(N-m, ft-lb, in-lb, kg-cm) selectable
- Auto power off after about 2 minutes idle



Model	EMTT-5E	EMTT-028E	EMTT-68E
Accuracy	$\pm 1\%$ CW/CCW	$\pm 1\%$ CW/CCW	$\pm 1\%$ CW/CCW
Square Drive (inches)	1/4" Drive	3/8" Drive	3/8" Drive
Max. Torque	5Nm / 3,69Ft/Lb 44,25In/Lb	28Nm / 20,65Ft/Lb 247,8In/Lb	68Nm / 50,1Ft/Lb 602In/Lb
Torque Measuring Range	0,50 – 5Nm	2,8 – 28Nm	6,8 – 68,00Nm
Resolution	0,1 Nm 0,001in/Lb 0,1Ft/Lb	0,1 Nm 0,001in/Lb 0,1Ft/Lb	0,1 Nm 0,001in/Lb 0,1Ft/Lb
Operation Mode	1st Peak /Peak hold/Track	1st Peak /Peak hold/Track	1st Peak /Peak hold/Track
Unit Selection	Nm, Inch/Lb, Ft/Lb, Kg/cm	Nm, Inch/Lb, Ft/Lb, Kg/cm	Nm, Inch/Lb, Ft/Lb, Kg/cm
Bright Led	6 LED ( 1 Red + 5 Green)	6 LED ( 1 Red + 5 Green)	6 LED ( 1 Red + 5 Green)
PC Connectivity	Yes USB cable supported	Yes USB cable supported	Yes USB cable supported
Buttons	5	5	5
Powered by	Mini USB AC/DC adaptor	Mini USB AC/DC adaptor	Mini USB AC/DC adaptor



Model	EMTT350E	EMTT815E	EMTT1000E	EMTT2000E
Accuracy	±1% CW/CCW	±0,5% CW/CCW	±0,5% CW/CCW	±0,5% CW/CCW
Square Drive (inches)	1/2" Drive	Male Hexagon 27mm	Male Hexagon 27mm	Male Hexagon 27mm
Max. Torque	350Nm / 258,1Ft/Lb 3098In/Lb	815Nm / 601Ft/Lbs	1000Nm / 738Ft/Lb	2000Nm / 1475Ft/Lb
Torque Measuring Range	35,00 – 350,00Nm	81,5,00 – 815,00Nm	100,00 – 1000,00Nm	200,00 – 2000,00Nm
Resolution	0,1 Nm 0,001in/Lb 0,1Ft/Lb	0,1 Nm 0,001in/Lb 0,1Ft/Lb	0,1 Nm 0,1Ft/Lb	0,1 Nm 0,1Ft/Lb
Operation Mode	1st Peak /Peak hold/Track	1st Peak /Peak hold/Track	1st Peak /Peak hold/Track	1st Peak /Peak hold/Track
Unit Selection	Nm, Inch/Lb, Ft/Lb, Kg/cm	Nm, Inch/Lb, Ft/Lb, Kg/cm	Nm, Ft/Lb	Nm, Ft/Lb
Bright Led	6 LED ( 1 Red + 5 Green)	6 LED ( 1 Red + 5 Green)	6 LED ( 1 Red + 5 Green)	6 LED ( 1 Red + 5 Green)
PC Connectivity	Yes USB cable supported	Yes USB cable supported	Yes USB cable supported	Yes USB cable supported
Buttons	5	5	5	5
Powered by	Mini USB AC/DC adaptor	Mini USB AC/DC adaptor	Mini USB AC/DC adaptor	Mini USB AC/DC adaptor